

AUTO CHEMISTRY ANALYZER ANA81-800



AUTO CHEMISTRY ANALYZER ANA81-800

Auto Chemistry Analyzer used to measure different chemicals and clinical chemistry of human biological samples. Used in Research, Hospital, Clinical chemistry, Laboratory, Pharmaceutical.
Also known as Routine biochemistry analysers.

ANA81-800 AUTO CHEMISTRY ANALYZER

150 Sample positions
160 Reaction cuvettes
180 Refrigerated reagent positions
Optical filter/fiber bragg grating selectable
800 Tests per hour (1200 Tests with ISE module)
Built-in sample barcode system optional
Probe with anti-collision function, liquid level detection function.



SPECIFICATIONS

Model	ANA81-800
Overall Performance	
Throughput	800 Tests/hour, 1200Tests/hour with ISE(Optional)
Analysis Method	End-point, Fixed-time, Rate(Kinetic)
Certificates	CE, FDA, ISO9001, ISO13485
Sample & Reagent System	
Sample Positions	150 sample positions
Reagent Positions	180 reagent positions
Sample Volume	1~70 µl
Reagent Volume	10~350 µl
Probe	Teflon coating, with anti-collision function, liquid level detection function
Probe Washing	Automatic washing interior and exterior
Reagent Cooling	Refrigerated tray with independent switch
Reaction System	
Temperature Control	Water bath, 37±0.1°C, real-time monitoring
Cuvettes	160 reusable cuvettes, optical length 6mm
Mixer Probe	Independent stirring
Washing	Automatic cuvettes washing
STAT Function	YES
Optical System	
Light Source	12 V/20 W halogen lamp/fiber bragg grating optional
Spectrophotometry	Post-spectral spectrophotometry
Wavelength	12 wavelengths from 340~800nm
Absorbance	0~3.5 Abs
Calibration & QC	

Calibration	Linear: K factor, 1-point, 2-point and multipoint linear Non-Linear: Spline, Polygon, Index, Ogarithm, Logit-4P, Logit-5P
Quality Control	Real-time QC, Westgard multi rule, Cumulative Sum Check, Twin Plot(2D)
Data Management	
Software	Windows 7/8/10, 32 or 64 bit
LIS System	Bi-direction, support HL7 protocol
Interface	LAN port access
Printer	External, multiple reporting mode available
Working Conditions	
Power Supply	AC220 V \pm 10% 50/60 HZ, 110 V \pm 10% 60 Hz, 1500 W
Temperature	15~30°C (\pm 2°C)
Water Consumption	Deionized water: <25L/H
Humidity	40%~85%
Size & Weight	
External Size (W*D*H)	1360x795x1155 mm
Net Weight	290 kg
Package Size (W*D*H)	1718x958x1427 mm
Gross Weight	400 kg

Centrifugen

Centrifugen

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: info@centrifugen.com | Website: centrifugen.com