

INCUBATOR SHAKER SHA26-0300



INCUBATOR SHAKER SHA26-0300

In Incubator Shaker, the constant agitation with uniform amplitude provides the optimum oxygen transfer to the cultures, leading to better and consistent yield. A variety of platforms and different laboratory accessories permits configuration to fulfill your demands.

Used in Cell Cultures, Cell Aeration, Microbiology, Increasing Solubility Rates, Metabolism Studies, Bacterial Cultures, Bacteriology.

Also known as Laboratory Incubator Shaker, Incubator Shaker.

SHA26-0300 INCUBATOR SHAKER

Integrate incubator and shaker

Save lab space

Compact designed, good temperature uniformity, low noise

Micro-processor controls temperature and shaking speed

Built-in time function

Friendly designed touch screen and operation panel

Cover can be widely angle opened, convenient to watch and pick sample

Equiped with cover switch

When the cover is open, air circulation, heating and shaking automatically stop

No temperature overshoot problem

Unique speed control circuit to ensure shaker smoothly starting to avoid liquid spilling

Circulation fan speed can be adjusted to avoid high-speed of the circulation fan making the sample volatilizing

Independent temperature alarm system

Heating is cut off when temperature is over the limited value

Alarm after program finished

Brushless DC motor, long life and free maintenance



SPECIFICATIONS

Model	SHA26-0300
Speed Range	50-300 rpm
Temperature	4°C~60°C @RT≤25°C
Temperature Accuracy	0.1°C
Temperature Stability @37°C	≤±0.3°C
Shaking Orbit	20 mm
Timing Range	1 min~99 h 59 min or continuous
Overall Dimension	385x560x320 mm
Weight	18.7 kg
Fuse	250 V,3 A/5 A, Φ5x20
Power	600 W
Power Supply	AC220 V/AC110, 50/60 Hz

Centrifugen

Centrifugen

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: info@centrifugen.com | Website: centrifugen.com