

SINGLE BEAM VISIBLE SPECTROPHOTOMET ER SPE11-0320



SINGLE BEAM VISIBLE SPECTROPHOTOMETER

SPE11-0320

Single beam specs measure absolute light intensity. It can perform photometric measurement, quantitative measurement, spectrum scanning, DNA/Protein analysis.

Used in Most suitable for quantitative determination assays and toxicological assays in environmental, industrial, pharmaceutical fields..

Also known as Vis Spectrometer, UV-Vis Spectrometer, Spectrometers, visible spectrophotometer.

SPE11-0320 SINGLE BEAM VISIBLE SPECTROPHOTOMETER

Wavelength range: 320nm-1100nm

Optical System: 1200 lines/mm line Czerny Turner Diffraction Grating monochromator ensures high resolution, high photometric accuracy and low stray light

Bandwidth: 2nm

Detector: Silicon Photodiode

Measurement Range with ultra-low Stray Light With its ultra-low stray light $\leq 0.05\%$ is achieved on wavelength range of 320 - 1100 nm

Sample size: A wide range of standard cuvettes can be used based on the sensitivity or sample volume requirements.

Sophisticated and simplified sample analysis software: The Sample analysis software deliver scanning, fixed wavelength analysis, quantitative analysis, data collection, storage, export, and reporting.

With additional feature of an easy access USB port available in the unit, which enables results to be stored directly to a USB memory stick for easy transfer of data.

Suspended posture optical system

24-bit high speed and high precision A/D conversion technique improves sensitivity

Can store up to 200 groups of data and 200 standard curves

Automatic wavelength setting

Automatic wavelength calibration and automatic deviation repair

USB port and parallel port

Inclusive of standard PC software



SPECIFICATIONS

Model	SPE11-0320
Wavelength Range	320-1100 nm
Wavelength Accuracy	± 0.5 nm
Wavelength Reproducibility	≤ 0.2 nm
Wavelength Repeatability	≤ 0.2 nm
Spectral Bandwidth	3 nm
Photometric Range	0.200 %T, -0.3-3 A, 0-9999 C
Photometric Accuracy	± 0.3 %T
Photometric Repeatability	≤ 0.15 %T
Stability	± 0.0001 A/hr at 500 nm
Baseline Flatness	± 0.0001 A/h
Stray Light	≤ 0.05 %T

Light Source	Tungsten-Halogen Lamp
Photometric Mode	≤0.05 %T
Software	USB
Gross Dimension (W/D/H)	460x380x180 mm
Display	LCD (228x64 pixel)
Noise	≤0.0005A
Weight (Net/Gross)	15 kg
Power	300 W
Power Supply	AC 220V/50Hz or AC110/60Hz

ACCESSORIES

Accessory Code	Name	Description	Unit
LS53371	Glass cuvette (10 mm)		4 pcs
LS53395	Dustproof cover		1 pc
LS53419	Software CD		1 pc
LS53431	USB Cable		1 pc
LS53443	Power cord		1 pc
LS53455	Softdog		1 pc

OPTIONAL ACCESSORIES

Accessory Code	Name	Description	Volume	Unit
LS53211	Single Position Water Jacketed Ambient Cell Holder	10 mm		
LS53223	4-Position Cell Holder	10 mm		
LS53235	4-Position Cell Holder	50 mm		
LS53247	4-Position Cell Holder	100 mm		
LS53271	Adjustable Cell Holder for Micro Cuvettes			
LS53283	Transparent Film Holder			
LS53295	Tube Holder			
LS53307	Thermostatic Controller			
LS53319	Auto Sampler			
LS53331	Auto Thermostatic Sampler			
LS53343	Micro Printer			
LS53355	Tungsten Lamp 6V, 10W (PH)			
LS53367	Tungsten Lamp 12V, 20W (PH)			
LS53379	Tungsten Lamp 12V, 20W (OSRAM)			
LS53403	Glass Cuvette	5x10x45	1.7 ml	Set (4 pcs)
LS53415	Glass Cuvette	10x10x45	3.5 ml	Set (4 pcs)
LS53427	Glass Cuvette	20x10x45	7 ml	Set (4 pcs)
LS53439	Glass Cuvette	30x10x45	10.5 ml	Set (4 pcs)
LS53451	Glass Cuvette	40x10x45	14 ml	Set (4 pcs)
LS53463	Glass Cuvette	50x10x45	17.5 ml	Set (4 pcs)
LS53475	Glass Cuvette	100x10x45	35 ml	Set (4 pcs)
LS53487	Quartz Cuvette	5x10x45	1.7 ml	Set (2 pcs)
LS53499	Quartz Cuvette	10x10x45	3.5 ml	Set (2 pcs)
LS53511	Quartz Cuvette	20x10x45	7 ml	Set (2 pcs)

LS53523	Quartz Cuvette	30x10x45	10.5 ml	Set (2 pcs)
LS53535	Quartz Cuvette	40x10x45	14 ml	Set (2 pcs)
LS53547	Quartz Cuvette	50x10x45	17.5 ml	Set (2 pcs)
LS53559	Quartz Cuvette	100x10x45	35 ml	Set (2 pcs)
LS53571	Micro Quartz Cuvette	10x2x2.5	50 ml	Set (2 pcs)
LS53583	Micro Quartz Cuvette	10x2x5	100 µl	Set (2 pcs)
LS53595	Micro Quartz Cuvette	10x2x10	200 µl	Set (2 pcs)
LS53607	Micro Quartz Cuvette	10x2x25	500 µl	Set (2 pcs)
LS53619	Micro Quartz Cuvette	10x2x45	700 µl	Set (2 pcs)
LS53631	Quartz Flow Cuvette			Set (2 pcs)
LS55199	Micro Quartz Cuvette	10x2x45		Set (2 pcs)

Centrifugen

Centrifugen

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: info@centrifugen.com | Website: centrifugen.com